



CTB2 - Customer Termination Box 2

Product Overview

The CTB2 is a universal enclosure that has been developed for housing fiber connectivity. The versatile design gives the CTB2 the ability to accommodate a number of connectivity solutions, splice only, splice and patch and even splitter modules.

The box is a high quality housing that can be supplied in a variety of colours. Internally, we are able to supply with either a plastic or metal module, to accommodate fibre storage cable management.

For splice only applications, the CTB2 is supplied with an internal splice cassette with 48F splice capacity and midspan storage space behind the cassette. Pre-tailed versions are also available with fanout cables, pre-installed.

Applications

- Future-proof FTTP deployments
- FTTA
- MDU
- Demarcation points

Features

- Robust / impact resistant
- Cost effective
- UV stable
- Multifunctional
- V0 Fire-rated (grey option for I/O)

Specifications

Dimensions	42 mm D x 150 mm W x 270 mm H
Weight	350g (Approximate Weight)
Mounting	Bracket or wall
Material	ABS, (Grey) Polycarbonate V0
Minimum Bend Radius	15 mm



Splice Only

The splice only configuration can hold up to 3 x 1:4 splitters. The boxes listed hold 1 x 1:4 and the splitter update kit is listed. Follow Application note CF2402_02

Ordering Information

Part number	Description
CFMDU-CTB2-B-P08-1X4-UNL	CFMDU - CTB2 - Distribution Node - 8f - Split/Splice - 1:4(2) - Black
CFMDU-BPS0F0-104-PIG-3-2	Splitters, De-ribbonised, 250um, PLC 1:4, Unterminated, 3m In 2m Out