



## CityFibre Aerial Hardware

### Bracket 22

A dropwire fixing consisting of a galvanised steel triangular bracket with three fixing holes and a welded loop. Designed to attach a dropwire clamp to timber at end users premises or on a multi pole route where no pole ring exists.



### Ordering Information

Part number	Description	Material	Size	Weight
CFMDU-TRI-BRKT-22	CFMDU - Anchoring Cable - Triangular Bracket - Bracket 22	Galvanised	83x44x38 mm	77 g
CFSDU-TRI-BRKT-22	CFSDU - Anchoring Cable - Triangular Bracket - Bracket 22	Galvanised	83x44x38 mm	77 g

### Bracket 32

A dropwire fixing consisting of a galvanised steel “J” shaped bracket with a welded loop and a plate with four holes at the other end. Designed to attach a dropwire clamp to timber or brickwork at end users premises where additional height clearance is required.



### Ordering Information

Part number	Description	Material	Add Cable Clearance	Length	weight
CFMDU-EXT-ARM-32	CFMDU - Dropwire Clamp - Extended Fixing Arm	Galvanised	175x190 mm	75x75 mm	580 g
CFSDU-EXT-ARM-32	CFSDU - Dropwire Clamp - Extended Fixing Arm	Galvanised	175x190 mm	75x75 mm	580 g

## Bracket 44

A dropwire fixing consisting of a galvanised steel “L” shaped bracket with a welded loop at one end and a plate with two holes at the other end. Designed to attach a dropwire clamp to brickwork at end users premises where further additional height clearance is required.



### Ordering Information

Part number	Description	Material	Add Cable Clearance	Length	Weight
CFMDU-BRACKET-44	CFMDU - Dropwire Clamp - Extended Fixing Arm	Galvanised	400x200 mm	150x100 mm	1.75Kg
CFSDU-BRACKET-44	CFSDU - Dropwire Clamp - Extended Fixing Arm	Galvanised	400x200 mm	150x100 mm	1.75Kg

## M6 Expanding Bolt (Type 1A)

Overhead single point fixing bolt.



### Ordering Information

Part number	Description	Material	Drill Size	Min Hole depth	Max Fixture thickness
CFMDU-EX-EYE-BOLT-8/10MM	CFMDU - Expanding Eye Bolt - Type 1A - 8-10mm Hole with 12mm ring	Zinc plated steel	8mm	45mm	93mm
CFSDU-EX-EYE-BOLT-8/10MM	CFSDU - Expanding Eye Bolt - Type 1A - 8-10mm Hole with 12mm ring	Zinc plated steek	8mm	45mm	93mm

## M6 Expanding Bolt (Type 2A)

Overhead single point fixing bolt



### Ordering Information

Part number	Description	Material	Drill Size	Min Hole depth	Max Fixture thickness
CFMDU-EX-EYE-BOLT-16MM	CFSDU - Expanding Eye Bolt - Type 2A - 16mm Hole with 14mm ring	Zinc plated steel	16mm	95mm	130mm
CFSDU-EX-EYE-BOLT-16MM	CFSDU - Expanding Eye Bolt - Type 2A - 16mm Hole with 14mm ring	Zinc plated steel	16mm	95mm	130mm

### Ordering Information

Part number	Description
CFMDU-Aerial-Hardware	Aerial Hardware