



# 10015776

**Hexatronic (ISCVM-8/MPB30269/GN1CT-2) FTTP - Blown Cable Microduct - External Open Duct Only - 7/4mm - Black & 4x Green Stripes UV MDPE - Empty Tube - Marked Property of Virgin Media {UOM: Ea / 1 = 1x 500m Drum}**

---

## Features

- For direct burial
- 7/4 mm microducts
- Low friction inner surface

## Application

The thick walled microduct are designed with an inner low friction surface that enables installation of air-blown fibers or nano cables. The thick inner wall of the microducts allow for installation directly into the ground without the need for additional protection.

## Design

7/4 mm microducts are optimized for installation of air-blown fibers and nano cables. The microducts have a solid low-friction inner surface for best blowing performance.

## Product Information

**Microducts:** HDPE

## Technical Information

Product Color	Black with 4 green stripes
Temperature, Operation [°C]	-40 to +60
Temperature, Storage [°C]	-40 to +60
Temperature, Installation [°C]	-20 to +50
Conformance	<p><b>Abrasion:</b> IEC60794-1-2-E2B(1)</p> <p><b>Kink:</b> IEC60794-1-2-E10, 20 x outer diameter</p> <p><b>Impact:</b> IEC60794-1-2-E4</p> <p><b>Crush:</b> IEC60794-1-2-E3</p> <p><b>Tensile:</b> IEC60794-1-2-E</p> <p><b>Bend:</b> IEC60794-1-2-E11A</p> <p><b>Torsion:</b> IEC60794-1-2-E</p> <p><b>Flexibility:</b> IEC60794-1-2-E8</p> <p><b>Inner Clearance:</b> IEC60794-5-20, IEC60794-5-10, Ann. D</p>
Marking	<p>Example of sheath marking, 1 time/meter:</p> <p>“HEXATRONIC Property of Virgin Media yymmddhh 8/MPB30269/GN1CT-2 Microduct 7/4 xxxxm”</p> <p>where yymmddhh= year, month, day and hour of manufacture, xxxxx=running meter marking</p>

Articles 1

Article name	Color	Layout	Bend Radius [mm]	Tensile Force, Installation [N]	Crush [N/100 mm]	Impact [J]	Dimensions [mm]	Weight [kg/km]	Length [m]
10015776 ISCV-M-8/MPB30269/GN1CT-2	Black with 4 x green stripes	7/4	70	230	2500	2.5	7	24	500